







DELPHION

No acti

Select CR**RESEARCH****PRODUCTS****INSIDE DELPHION**[Log Out](#) | [Work Files](#) | [Saved Searches](#)[My Account](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#)**The Delphion Integrated View**Get Now: ☒ [PDF](#) | [File History](#) | [Other choices](#)Tools: Add to Work File: [Create new](#)View: [INPADOC](#) | Jump to: [Top](#) Go to: [Derwent](#)Title: **JP06051117A2: POLARIZING FILM FOR LIQUID CRYSTAL DISPL**Derwent Title: Durable, heat-resistant polarising film for LCD - has protective layer of thermoplastic satd. norbornane series resin on one or both faces providing low double refraction [\[Derwent Record\]](#)Country: **JP** JapanKind: **A** (See also: [JP03297450B2](#))Inventor: **TAKAHASHI SHINICHI;
HANI TSUTOMU;
NATSUUME YOSHIO;
ICHIKAWA RINJIRO;
HASHIMOTO KENJI;**Assignee: **NIPPON ZEON CO LTD
FUJIMORI KOGYO KK**
[News, Profiles, Stocks and More about this company](#)Published / Filed: **1994-02-25 / 1991-07-22**Application Number: **JP1991000205522**IPC Code: **IPC-7: G02B 5/30; G02F 1/1335;**Priority Number: **1991-07-22 JP1991000205522**Abstract: **PURPOSE:** To improve the resistance to water, moisture and heat, transparency and adhesion to adhesive of a polarizing film by laminating a sheet of a thermoplastic saturated norbornene-base resin on at least one side of the polarizing film as the protective layer.**CONSTITUTION:** A sheet of a thermoplastic saturated norbornene-base resin is laminated on at least one side of a polarizing film as a protective layer. The polarizing film functions as a polarizer, and is a PVA iodine-base polarizing film or a dye-base polarizing film obtained by adsorbing a dichromatic dye on a PVA film and orienting the film. The thermoplastic saturated norbornene-base resin sheet as the protective layer is formed by the soln. casting method, and the resin is dissolved in a solvent in this case. A solvent having $\geq 100^{\circ}\text{C}$ or preferably $\geq 120^{\circ}\text{C}$ b.p. is used, and the solvent has to uniformly dissolve the resin even if the solid content is controlled to $\geq 10\text{wt.}\%$.**COPYRIGHT:** (C)1994,JPO&JapioINPADOC Legal Status: None [Get Now: Family Legal Status Report](#)Designated Country: **EP KR US**Family: [Show 3 known family members](#)Forward References: [Go to Result Set: Forward references \(5\)](#)[PDF](#)

	Patent	Pub.Date	Inventor	Assignee	Title
	US6961178	2005-11-01	Sugino; Youchirou	Nitto Denko Corporation	Polarizing film, of liquid crystal disp polarizing film
	US6840635	2005-01-11	Maeda; Hiroe	Nitto Denko Corporation	Polarizer and me producing the sai
	US6552145	2003-04-22	Okada; Yasumasa	Sekisui Chemical Co., LTD	Polarizer protecti
	US5833878	1998-11-10	Shinohara; Hironobu	JSR Corporation	Liquid crystal disj
	US5516456	1996-05-14	Shinohara; Hironobu	Japan Synthetic Rubber Co., Ltd.	Liquid crystal disj

Other Abstract
Info:

[DERABS C93-058928](#)



[Nominate this for the Gallery...](#)

Copyright © 1997-2006 The

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Cont](#)